

SALBAK ROLLS P.V.C.

Technical Specification

Raw Material	PVC	
Thickness	0.25mm – 10 Thou 0.50mm – 20 Thou 0.75mm – 30 Thou	
Tensile Strength	10 & 20 Thou 30 Thou	Warp – 190kg/cm ² Weft - 180kg/cm ² Warp – 200kg/cm ² Weft – 190kg/cm ²
Tear Strength	10- & 20 Thou 30 Thou	Warp – 6kg/mm Weft – 6kg/mm Warp – 7kg/mm Weft – 6kg/mm
Elongation (%)	10 & 20 Thou 30 Thou	Warp – 240 Weft - 260 Warp – 250 Weft – 250
Heat Shrinkage (%)	10 & 20 Thou 30 Thou	Warp – Minus 5 Weft – Plus 2 Warp – Minus 3.5 Weft – Plus 3.0
Width	10, 20 & 30 Thou – 137cm	
Weight	10 Thou – 320g/m ² 20 Thou – 640g/m ² 30 Thou – 960/m ²	
Fire Retardant	To BS5438 and MVSS 302	
UV Resistant	Yes	
Roll Length	20 Thou – 50m	

The information contained in this document is correct to the best of our knowledge but results may vary depending on the conditions under which the material is used and consequently recommendations are made without warranty or guarantee.